




Εύκαμπτη ταινία led / Flexible led strip

TORA

Κωδικός / Art. No. : 500118

24Vdc

19.2 Watt/m

RGBW

60led/m

IP67


3 ΧΡΟΝΙΑ ΕΓΓΥΗΣΗ
YEARS WARRANTY

Τεχνικά χαρακτηριστικά / Technical data

Κατανάλωση ενέργειας / Power consumption	19.2 kWh/1000h/m
Ονομαστική Ισχύς / Rated wattage	19.2 W/m
Τάση λειτουργίας / Operating Voltage	24Vdc
Ρεύμα λειτουργίας / Typical operating Current	0.8 A/m
Κατηγορία προστασίας / Protection class	III
Ρύθμιση έντασης φωτισμού / Dimming	PWM (Dali / DMX512 / RF / Push Button)
Φωτεινή απόδοση / Luminous Efficacy	R30, G64, B14, W95 (lumen/watt)
Φωτεινή ροή / Typical Luminus Flux	R144, G307, B67, W456 (lumen/m)
Γωνία φωτισμού / Led beam angle	120°
Χρώμα / Color	RGBW
Μήκος κύματος / Wavelength	R623±5, G520±, B465±5 (nm)
Θερμοκρασία χρώματος / Typical CCT	3000K
Βαθμός χρωματικής απόδοσης / Typical CRI	>80
Ανοχή Χρώματος /Color Tolerance	5 SDCM
Διάρκεια ζωής στους 25 °C / Rated life time at 25 °C	30.000 ώρες/hours
Βαθμός στεγανότητας / Ingress protection	IP67
Λειτουργία σε θερμοκρασία περιβάλλοντος / Ambient working Temp. ta	-20...+50°C
Διαστάσεις (ΜxΠxΥ) / Dimension (LxWxH)	5000 x 12.4 x 4.2(mm)
Μέγιστο μήκος λειτουργίας / Max. operating Length	5 μέτρα / 5 meters
Αριθμός Led / Led units	60 led/μέτρο / 60 led/meter
Απόσταση μεταξύ led / Distance between led	16.67 mm
Σημείο κοπής / Cutting point	Ανά 6 led (100mm) / Per 6 led (100mm)
Συσκευασία / Packing	5 μέτρα / 5 meters
EAN	5206704006743
Εγγύηση / Warranty	3 χρόνια / 3 years

(Όλες οι τιμές μπορεί να έχουν μία απόκλιση +/-5% - All values can have a tolerance of +/- 5%)

Σχέδιο - Διαστάσεις / Drawing - Dimensions



Κατάλληλη για εσωτερικούς - εξωτερικούς χώρους με υψηλή υγρασία.
Κατάλληλη για εσωτερικούς - εξωτερικούς χώρους με υψηλή συγκέντρωση αιωρούμενων σωματιδίων.
Δυνατότητα παραμονής σε νερό για μικρό χρονικό διάστημα.
Suitable for indoor - outdoor areas with high humidity.
Suitable for indoor - outdoor areas with high concentration of suspended particles.
Can stay in water for a short time.

Light efficiency:

30 Lumen/Watt


Light quality:

CRI: 0.0

Color temperature:

0 K

Output: 144 Lumen Power consumption: 4.8




Product name:

TQRA 19.2Watt 60led 24V IP67
RGBW(RED)


Item number:

500118


Spectral distribution



Color coordinates



White color point




CRI R values

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0.0	0.0	0.0	0.0	0.0	0.684	0.299	0.524	0.344	n/a

Beam details



Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
120°	166.7°	178.4°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
44.4 cd	74.1%	49.2%

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
44lx	11lx	5lx	3lx	2lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx
4.1fcd	1fcd	0.5fcd	0.3fcd	0.2fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd

Power scope



Power	Power factor	
4.8 W	1.0	

Voltage	Current	
24.0 V	0.200 A	

Light efficiency:

64 Lumen/Watt


Light quality:

CRI: 0.0

Color temperature:

0 K

Output: 307 Lumen Power consumption: 4.8







Product name:

**TΩRA 19.2Watt 60led 24V IP67
RGBW(GREEN)**

Item number:

500118




CRI R values

A blank coordinate grid with x and y axes. The x-axis is labeled with R1 through R15, and the y-axis is labeled with Q1 through Q5. The grid consists of 15 columns and 5 rows.

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color diviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0.0	0.0	0.0	0.0	0.0	0.150	0.724	0.053	0.382	n/a

Beam details



Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
120°	166.6°	176.2°


Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
93.5 cd	74.9%	49.4%

Beam intensities from 1-20m

[illegible]

Power scope



Power	Power factor	
4.8 W	1.0	

Voltage	Current	
24.0 V	0.200 A	


Light efficiency:



Light quality:



Color temperature:



Product name:


**TΩRA 19.2Watt 60led 24V IP67
RGBW(BLUE)**

Item number:


500118

Output: 67.4 Lumen Power consumption: 4.8


Spectral distribution



Color coordinates



White color point




CRI R values



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color diviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0.0	0.0	0.0	0.0	0.0	0.140	0.045	0.172	0.083	n/a

Beam details



Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
120°	167.1°	178°


Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
20.4 cd	73.8%	48.8%

Beam intensities from 1-20m

[illegible]

Power scope



Power	Power factor	
4.8 W	1.0	

Voltage	Current	
24.0 V	0.200 A	

Light efficiency:

95 Lumen/Watt


Light quality:

CRI: 82.8

Color temperature:

3000 K

Output: 456 Lumen Power consumption: 4.8




Product name:

**TQRA 19.2Watt 60led 24V IP67
RGBW(WHITE)**


Item number:

500118


Spectral distribution




Color coordinates



White color point




CRI R values



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3000 K	82.8	5.5	85.5	95.4	82.5	0.437	0.404	0.251	0.348	0.0007

Beam details



Beam angles

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
120°	165.1°	175.7°


Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
149 cd	76.0%	51.0%

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
148lx	37lx	16lx	9lx	6lx	4lx	3lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx
13.8fcd	3.4fcd	1.5fcd	0.9fcd	0.6fcd	0.4fcd	0.3fcd	0.2fcd	0.2fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0fcd	0fcd	0fcd	0fcd

Power scope



Power	Power factor	
4.8 W	1.0	

Voltage	Current	
24.0 V	0.200 A	